

Package: evsim (via r-universe)

May 18, 2026

Title Electric Vehicle Charging Sessions Simulation

Version 1.7.1

Maintainer Marc Cañigüeral <marccanyigüeral@gmail.com>

Description Simulation of Electric Vehicles charging sessions using Gaussian models, together with time-series power demand calculations.

License GPL-3

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Imports MASS, dplyr, lubridate, purrr, rlang, tidyr, jsonlite, ggplot2,

Suggests carrier, mirai, spelling, testthat (>= 3.0.0)

Depends R (>= 4.1.0)

URL <https://github.com/resourcefully-dev/evsim/>,
<https://resourcefully-dev.github.io/evsim/>

BugReports <https://github.com/resourcefully-dev/evsim/issues>

Language en-US

Config/testthat/edition 3

Config/pak/sysreqs libicu-dev

Repository <https://resourcefully-dev.r-universe.dev>

Date/Publication 2025-12-19 16:37:22 UTC

RemoteUrl <https://github.com/resourcefully-dev/evsim>

RemoteRef HEAD

RemoteSha 1a6e67ae58d57d09c1cd7af428d9317389f05e68

Contents

adapt_charging_features	2
add_charging_infrastructure	3
expand_sessions	5
get_charging_rates_distribution	6
get_custom_ev_model	6
get_demand	8
get_evmodel_parameters	9
get_evmodel_summary	10
get_occupancy	11
get_user_profiles_distribution	12
plot_occupancy_duration_curve	13
read_ev_model	14
save_ev_model	14
simulate_sessions	15
Index	17

adapt_charging_features
Adapt charging features

Description

Calculate connection and charging times according to energy, power and time resolution

Usage

```
adapt_charging_features(  
  sessions,  
  time_resolution = 15,  
  power_resolution = 0.01  
)
```

Arguments

sessions	tibble, sessions data set in standard format marked by {evprof} package. The minimum required variables are: <ul style="list-style-type: none"> • ConnectionStartDateTime (POSIXct) • ConnectionHours (numeric) • Power (numeric) • Energy (numeric)
time_resolution	integer, time resolution (in minutes) of the sessions' datetime variables
power_resolution	numeric, power resolution (in kW) of the sessions' power

Details

All sessions' Power must be higher than 0, to avoid NaN values from dividing by zero. The ConnectionStartDateTime is first aligned to the desired time resolution, and the ConnectionEndDateTime is calculated according to the ConnectionHours. The ChargingHours is recalculated with the values of Energy and Power, limited by ConnectionHours. Finally, the charging times are also calculated.

Value

tibble

Examples

```
suppressMessages(library(dplyr))

sessions <- head(evsim::california_ev_sessions, 10)

sessions %>%
  select(ConnectionStartDateTime, ConnectionEndDateTime, Power)

adapt_charging_features(
  sessions,
  time_resolution = 60,
  power_resolution = 0.01
) %>%
  select(ConnectionStartDateTime, ConnectionEndDateTime, Power)

adapt_charging_features(
  sessions,
  time_resolution = 15,
  power_resolution = 1
) %>%
  select(ConnectionStartDateTime, ConnectionEndDateTime, Power)
```

add_charging_infrastructure

Assign a charging station to EV charging sessions

Description

Variable ChargingStation and Socket will be assigned to the sessions tibble with a name pattern being: names_prefix + "CHS" + number

Usage

```
add_charging_infrastructure(
  sessions,
  resolution = 15,
  min_stations = 0,
  n_sockets = 2,
  names_prefix = NULL,
  duration_th = 0
)
```

Arguments

sessions	tibble, sessions data set in standard format marked by {evprof} package
resolution	integer, time resolution in minutes
min_stations	integer, minimum number of charging stations to consider
n_sockets	integer, number of sockets per charging station
names_prefix	character, prefix of the charging station names (optional)
duration_th	integer between 0 and 100, minimum share of time (in percentage) of the "occupancy duration curve" (see function plot_occupancy_duration_curve). This is used to avoid sizing a charging infrastructure to host for example 100 vehicles when only 5% of time there are more than 80 vehicles connected. Then, setting duration_th = 5 will ensure that we don't over-size the charging infrastructure for the 100 vehicles. It is recommended to find this value through multiple iterations.

Value

tibble

Examples

```
# Assign a `ChargingStation` to every session according to the occupancy
sessions_infrastructure <- add_charging_infrastructure(
  sessions = head(evsim::california_ev_sessions, 50),
  resolution = 60
)
print(unique(sessions_infrastructure$ChargingStation))

# Now without considering the occupancy values that only represent
# a 10% of the time
sessions_infrastructure <- add_charging_infrastructure(
  sessions = head(evsim::california_ev_sessions, 50),
  resolution = 60, duration_th = 10
)
print(unique(sessions_infrastructure$ChargingStation))
```

expand_sessions	<i>Expand sessions along time slots</i>
-----------------	---

Description

Every session in `sessions` is divided in multiple time slots with the corresponding Power consumption, among other variables.

Usage

```
expand_sessions(sessions, resolution)
```

Arguments

<code>sessions</code>	tibble, sessions data set in standard format marked by <code>evprof</code> package
<code>resolution</code>	integer, time resolution (in minutes) of the time slots

Details

The `Power` value is calculated for every time slot according to the original required energy. The columns `PowerNominal`, `EnergyRequired` and `FlexibilityHours` correspond to the values of the original session, and not to the expanded session in every time slot. The column `ID` shows the number of the time slot corresponding to the original session.

Value

tibble

Examples

```
library(dplyr)

sessions <- head(evsim::california_ev_sessions, 10)
expand_sessions(
  sessions,
  resolution = 60
)
```

get_charging_rates_distribution
Charging rates distribution

Description

Get charging rates distribution in percentages from a charging sessions data set

Usage

```
get_charging_rates_distribution(sessions, unit = "year", power_interval = NULL)
```

Arguments

sessions	tibble, sessions data set in standard format marked by {evprof} package
unit	character. Valid base units are second, minute, hour, day, week, month, bimonth, quarter, season, halfyear and year. It corresponds to unit parameter in lubridate::floor_date function.
power_interval	numeric, interval of kW between power rates. It is used to round the Power values into this interval resolution. It can also be NULL to use all the original Power values.

Value

tibble

Examples

```
get_charging_rates_distribution(evsim::california_ev_sessions, unit = "year")
```

get_custom_ev_model *Create the custom EV model*

Description

Get the EV model object of class evmodel

Usage

```
get_custom_ev_model(  
  names,  
  months_lst = list(1:12, 1:12),  
  wdays_lst = list(1:5, 6:7),  
  parameters_lst,  
  connection_log,  
  energy_log,  
  data_tz  
)
```

Arguments

<code>names</code>	character vector with the given names of each time-cycle model
<code>months_lst</code>	list of integer vectors with the corresponding months of the year for each time-cycle model
<code>wdays_lst</code>	list of integer vectors with the corresponding days of the week for each time-cycle model (week start = 1)
<code>parameters_lst</code>	list of tibbles corresponding to the GMM parameters of every time-cycle model
<code>connection_log</code>	logical, true if connection models have logarithmic transformations
<code>energy_log</code>	logical, true if energy models have logarithmic transformations
<code>data_tz</code>	character, time zone of the original data (necessary to properly simulate new sessions)

Value

object of class `evmodel`

Examples

```
# For workdays time cycle  
workdays_parameters <- dplyr::tibble(  
  profile = c("Worktime", "Visit"),  
  ratio = c(80, 20),  
  start_mean = c(9, 11),  
  start_sd = c(1, 4),  
  duration_mean = c(8, 4),  
  duration_sd = c(0.5, 2),  
  energy_mean = c(15, 6),  
  energy_sd = c(4, 3)  
)  
  
# For weekends time cycle  
weekends_parameters <- dplyr::tibble(  
  profile = "Visit",  
  ratio = 100,  
  start_mean = 12,  
  start_sd = 4,
```

```

    duration_mean = 3,
    duration_sd = 2,
    energy_mean = 4,
    energy_sd = 4
  )

parameters_lst <- list(workdays_parameters, weekends_parameters)

# Get the whole model
ev_model <- get_custom_ev_model(
  names = c("Workdays", "Weekends"),
  months_lst = list(1:12, 1:12),
  wdays_lst = list(1:5, 6:7),
  parameters_lst = parameters_lst,
  connection_log = FALSE,
  energy_log = FALSE,
  data_tz = "Europe/Amsterdam"
)

```

get_demand

Time-series EV demand

Description

Obtain time-series of EV demand from sessions data set

Usage

```
get_demand(sessions, dtm_seq = NULL, by = "Profile", resolution = 15)
```

Arguments

sessions	tibble, sessions data set in standard format marked by {evprof} package
dtm_seq	sequence of datetime values that will be the datetime variable of the returned time-series data frame.
by	character, being 'Profile' or 'Session'. When by='Profile' each column corresponds to an EV user profile.
resolution	integer, time resolution (in minutes) of the sessions datetime variables. If dtm_seq is defined this parameter is ignored.

Details

Note that the time resolution of variables ConnectionStartDateTime and ChargingStartDateTime must coincide with resolution parameter. For example, if a charging session in sessions starts charging at 15:32 and resolution = 15, the load of this session won't be computed. To solve this, the function automatically aligns charging sessions' start time according to resolution, so following the previous example the session would start at 15:30.

Value

time-series tibble with first column of type datetime

Examples

```
suppressMessages(library(lubridate))
suppressMessages(library(dplyr))

# Get demand with the complete datetime sequence from the sessions
sessions <- head(evsim::california_ev_sessions, 100)
demand <- get_demand(
  sessions,
  by = "Session",
  resolution = 60
)
print(demand)

# Get demand with a custom datetime sequence and resolution of 15 minutes
sessions <- head(evsim::california_ev_sessions_profiles, 100)
dtm_seq <- seq.POSIXt(
  as_datetime(dmy(08102018)) %>% force_tz(tz(sessions$ConnectionStartDateTime)),
  as_datetime(dmy(11102018)) %>% force_tz(tz(sessions$ConnectionStartDateTime)),
  by = "15 mins"
)
demand <- get_demand(
  sessions,
  dtm_seq = dtm_seq,
  by = "Profile",
  resolution = 15
)
print(demand)
```

get_evmodel_parameters

Get evmodel parameters in a list

Description

Every time cycle is an element of the returned list, containing a list with the user profile as elements, each one containing the ratio and the corresponding tables with the statistic parameters of connection and energy GMM.

Usage

```
get_evmodel_parameters(evmodel)
```

Arguments

evmodel object of class evmodel

Value

list

Examples

```
get_evmodel_parameters(evsim::california_ev_model)
```

get_evmodel_summary *Get evmodel parameters in a list of summary tables*

Description

Every time cycle is an element of the returned list, containing a table with a user profile in every row and the mean and standard deviation values of the GMM variables (connection duration, connection start time and energy). If the energy models were built by charging rate, the average mean and sd are provided without taking into account different charging rates (this information is lost in this summary).

Usage

```
get_evmodel_summary(evmodel)
```

Arguments

evmodel object of class evmodel

Value

list

Examples

```
get_evmodel_summary(evsim::california_ev_model)
```

get_occupancy	<i>Time-series EV occupancy</i>
---------------	---------------------------------

Description

Obtain time-series of simultaneously connected EVs from sessions data set

Usage

```
get_occupancy(sessions, dtm_seq = NULL, by = "Profile", resolution = 15)
```

Arguments

sessions	tibble, sessions data set in standard format marked by {evprof} package
dtm_seq	sequence of datetime values that will be the datetime variable of the returned time-series data frame.
by	character, being 'Profile' or 'Session'. When by='Profile' each column corresponds to an EV user profile.
resolution	integer, time resolution (in minutes) of the sessions datetime variables. If dtm_seq is defined this parameter is ignored.

Details

Note that the time resolution of variable `ConnectionStartDateTime` must coincide with `resolution` parameter. For example, if a charging session in `sessions` starts charging at 15:32 and `resolution = 15`, the load of this session won't be computed. To solve this, the function automatically aligns charging sessions' start time according to `resolution`, so following the previous example the session would start at 15:30.

Value

time-series tibble with first column of type datetime

Examples

```
library(lubridate)
library(dplyr)

# Get occupancy with the complete datetime sequence from the sessions
sessions <- head(evsim::california_ev_sessions, 100)
connections <- get_occupancy(
  sessions,
  by = "ChargingStation",
  resolution = 60
)
print(connections)

# Get occupancy with a custom datetime sequence and resolution of 15 minutes
```

```
sessions <- head(evsim::california_ev_sessions_profiles, 100)
dtm_seq <- seq.POSIXt(
  as_datetime(dmy(08102018)) %>% force_tz(tz(sessions$ConnectionStartDateTime)),
  as_datetime(dmy(11102018)) %>% force_tz(tz(sessions$ConnectionStartDateTime)),
  by = "15 mins"
)
connections <- get_occupancy(
  sessions,
  dtm_seq = dtm_seq,
  by = "Profile"
)
print(connections)
```

get_user_profiles_distribution
User profiles distribution

Description

Get the user profiles distribution from the original data set used to build the model

Usage

```
get_user_profiles_distribution(evmodel)
```

Arguments

evmodel object of class evmodel

Value

tibble

Examples

```
get_user_profiles_distribution(evsim::california_ev_model)
```

`plot_occupancy_duration_curve`*Plot the occupancy duration curve*

Description

This term is based on the "load duration curve" and is useful to see the behavior of occupancy over the time in your charging installation. The steeper the curve, the shorter the duration that higher number of connections are sustained. Conversely, the flatter the curve, the longer the duration that higher number of connections are sustained. This information is crucial for various purposes, such as infrastructure planning, capacity sizing, and resource allocation.

Usage

```
plot_occupancy_duration_curve(  
  sessions,  
  dttm_seq = NULL,  
  by = "Profile",  
  resolution = 15  
)
```

Arguments

<code>sessions</code>	tibble, sessions data set in standard format marked by {evproof} package
<code>dttm_seq</code>	sequence of datetime values that will be the datetime variable of the returned time-series data frame.
<code>by</code>	character, being 'Profile' or 'Session'. When by='Profile' each column corresponds to an EV user profile.
<code>resolution</code>	integer, time resolution (in minutes) of the sessions datetime variables. If <code>dttm_seq</code> is defined this parameter is ignored.

Value

ggplot

Examples

```
library(dplyr)  
  
sessions <- head(evsim::california_ev_sessions_profiles, 100)  
plot_occupancy_duration_curve(  
  sessions,  
  by = "Profile",  
  resolution = 15  
)
```

read_ev_model	<i>Read EV model</i>
---------------	----------------------

Description

Read an EV model JSON file and convert it to object of class evmodel

Usage

```
read_ev_model(file)
```

Arguments

file path to the JSON file

Value

object of class evmodel

Examples

```
ev_model <- california_ev_model # Model of example  
save_ev_model(ev_model, file = file.path(tempdir(), "evmodel.json"))  
read_ev_model(file = file.path(tempdir(), "evmodel.json"))
```

save_ev_model	<i>Save the EV model</i>
---------------	--------------------------

Description

Save the EV model object of class evmodel to a JSON file

Usage

```
save_ev_model(evmodel, file)
```

Arguments

evmodel object of class evmodel
file character string with the path or name of the file

Value

nothing but saves the evmodel object in a JSON file

Examples

```
ev_model <- california_ev_model # Model of example

save_ev_model(ev_model, file = file.path(tempdir(), "evmodel.json"))
```

simulate_sessions *Simulation of EV sessions*

Description

Simulate EV charging sessions given the `evmodel` object and other contextual parameters.

Usage

```
simulate_sessions(
  evmodel,
  sessions_day,
  user_profiles,
  charging_powers,
  dates,
  resolution
)
```

Arguments

<code>evmodel</code>	object of class <code>evmodel</code> built with <code>{evprof}</code>
<code>sessions_day</code>	tibble with variables <code>time_cycle</code> (names corresponding to <code>evmodel\$models\$time_cycle</code>) and <code>n_sessions</code> (number of daily sessions per day for each time-cycle model)
<code>user_profiles</code>	tibble with variables <code>time_cycle</code> , <code>profile</code> , <code>ratio</code> and optionally <code>power</code> . It can also be <code>NULL</code> to use the <code>evmodel</code> original user profiles distribution. The powers must be in kW and the ratios between 0 and 1. The user profiles with a value of power will be simulated with this specific charging power. If power is <code>NA</code> then it is simulated according to the ratios of next parameter <code>charging_powers</code> .
<code>charging_powers</code>	tibble with variables <code>power</code> and <code>ratio</code> . The powers must be in kW and the ratios between 0 and 1. This is used to simulate the charging power of user profiles without a specific charging power in <code>user_profiles</code> parameter.
<code>dates</code>	date sequence that will set the time frame of the simulated sessions
<code>resolution</code>	integer, time resolution (in minutes) of the sessions datetime variables

Details

Some adaptations have been done to the output of the Gaussian models: the minimum simulated energy is considered to be 1 kWh, while the minimum connection duration is 30 minutes.

Value

tibble

Examples

```
library(dplyr)
library(lubridate)

# Get the example `evmodel`
ev_model <- evsim::california_ev_model

# Simulate EV charging sessions, considering that the Worktime sessions
# during Workdays have 11 kW, while all Visit sessions charge at 3.7kW or
# 11kW, with a distribution of 30% and 70% respectively.

simulate_sessions(
  ev_model,
  sessions_day = tibble(
    time_cycle = c("Workday", "Weekend"),
    n_sessions = c(15, 10)
  ),
  user_profiles = tibble(
    time_cycle = c("Workday", "Workday", "Weekend"),
    profile = c("Visit", "Worktime", "Visit"),
    ratio = c(0.5, 0.5, 1),
    power = c(NA, 11, NA)
  ),
  charging_powers = tibble(
    power = c(3.7, 11),
    ratio = c(0.3, 0.7)
  ),
  dates = seq.Date(today(), today()+days(4), length.out = 4),
  resolution = 15
)
```

Index

`adapt_charging_features`, [2](#)
`add_charging_infrastructure`, [3](#)

`expand_sessions`, [5](#)

`get_charging_rates_distribution`, [6](#)
`get_custom_ev_model`, [6](#)
`get_demand`, [8](#)
`get_evmodel_parameters`, [9](#)
`get_evmodel_summary`, [10](#)
`get_occupancy`, [11](#)
`get_user_profiles_distribution`, [12](#)

`plot_occupancy_duration_curve`, [13](#)

`read_ev_model`, [14](#)

`save_ev_model`, [14](#)
`simulate_sessions`, [15](#)